

#### Product Overview

Valiant's Enigmättron-C is an integrated router, firewall and data encryption equipment with extremely advanced features that may be installed to secure critical infrastructure such as Sub-Stations, Smart Grid Distribution Systems, Airport and Railway IT Networks as well as Financial Infrastructure such as Banks and Payment Processing Gateways.

The Enigmättron-C may also be installed in centrally managed networks consisting of multiple branch offices and edge locations to provide secure communications between ATMs, Point-Of-Sale Terminals and their corresponding back-end Central Servers.



Access to Enigmättron-C is password protected with advanced firewall capabilities that meet and exceed NERC as well as all mandatory requirements of Password Protection and Control as provided in the GR-815-CORE-2 specifications. Enigmättron-C can optionally be managed centrally from a RADIUS Server to provide enhanced levels of access security and centralized password management and control.

#### Enigmättron-C provides Comprehensive Protection for:

- IP Networks, including all types of Data, Voice and Video over IP applications
- MPLS meshed networks
- Metro Ethernet and VPLS networks

#### Firewall - Features and Capabilities:

- Deep Packet Inspection
- Per-frame/packet authentication
- Firewall
  - Port (Soft) based
  - MAC based
  - IP Address based
- IP Domain based
  - White List and Black List options
  - White List Exception allowed and Blocks all other traffic by default (system default mode)
- Black List Exception blocked and Allows all other traffic by default
- Seamless scalability
- Infrastructure neutral
- Transparent to network and applications
- Easy installation and management.

#### Interfaces:

- Total Number of Interfaces : 5
  - Four 10/100 RJ45 locally switched network interfaces to the local (trusted) network
  - One 10/100/1000 RJ45 network interface to the WAN (untrusted) network
- Integrated four-port Ethernet switch
- Auto MDI/X (straight or crossover Ethernet cable correction)
- USB serial port for local access and configuration.

#### Applications:

- Utilities: Electric generation, transmission and distribution
- Smart Grid Distribution Systems
- Oil & Gas production, pipelines
- Remote nodes in SCADA multi-drop networks
- Railway and Airport Infrastructure
- Financial Infrastructure such as Banks and Payment Processing Gateways
- Law Enforcement
- Distributed networks consisting of multiple edge locations such as ATMs, Point-Of-Sale Terminals and their corresponding back-end central Servers.

#### Firewall and Security:

- Secure Boot
- Firewall Security:
  - Inclusion Policy - Access Control based upon White List IP addresses, MAC address and IP Domain
  - Exclusion Policy - Access Control based on Black List
- Continuous monitoring of the TLS connection to nullify MitM attacks
- Resistance to Denial of Service (DoS) Attack
- Encrypted Firmware Updates
- Non-volatile Access Log with capability to "fingerprint" all successful and failed log-in attempts and keep a log of the IP and MAC addresses of all successful and failed logins / login attempts
- SNMP trap generation, along with LED and external alarm indication
- Password Protection with password strength monitor
- RADIUS Password Authentication
- SSH (Secure Access Control) with encrypted Password Protection

**Firewall / Router Throughput:**

- ≤90Mbps

**Supported Data Encryption Algorithms:**

- 3DES, AES128, AES192, AES256 Encryption Algorithm

**Maximum Encrypted Data Throughput:**

- ≤12Mbps with AES256 Encryption Algorithm

**Network Support:**

- IPv4 and IPv6 Routing
- Ethernet
- VLAN tag preservation
- MPLS tag preservation
- IPv4
- Secure NTP (Client).

**Monitoring and Access Control:**

- Password Strength Monitor
- Device Management and Alarm Monitoring
- Command Line Interface - Telnet, SSH
- SNMPv2 Alarm Monitoring
- Alarm condition detection and reporting (traps and SNMP alarm table)
- Syslog
- Audit Log

**Indicators:**

- System Status LED
- Power LED

**Power:**

- Power: 1+0 and 1+1 Redundant Power Supply Options.
- 100~240VAC, 50/60Hz
- 18VDC ~ 60VDC
- 85VDC ~ 140VDC
- Power consumption: 9W at maximum load

**Environmental:**

- Operational:
  - Temperature -20C to +60C (-4F to 140F),
  - Humidity up to 95% R.H. (Non-condensing at 60C)
  - Cold start: temperature -10C
  - Maximum Operational Humidity 95% R.H. (Non-condensing)

**Regulatory:**

Emissions	As per CISPR 22 / EN55022 Class A
CE and FCC	Part 15 Subpart A
Immunity	EN55024, En61000

**EMI, EMC, Surge Withstand and other Compliances**

EN 50081-2	EN 50082-2	IEC 60068-2-29
IEC 61000-4-6 (Conducted Immunity)	IEC 60068-2-6	IEC 60068-2-2
IEC 60068-2-78	IEC 60068-2-1	IEC 60068-2-14
CISPR 22 / EN55022 Class B (Conducted Emission and Radiated Emission)		
IS 9000 (Part II Sec. 1-4, Part III Sec. 1-5, Part IV, Part 14 Sec. 1-3)		
IEC 60870-2-1	IEC 61000-4-5	IEC 61000-4-12
IEC 61000-4-3 (Radiated Immunity)	IEC 61000-4-8	IEC 61000-4-16
IEC 61000-4-2	IEC 61000-4-10	Telcordia GR-1089
IEC 61000-4-4	IEC 61000-4-11	Surge and Power Contact

- ESD, Voltage and Surge Withstand: Meets and exceeds IEC 61000-4-2, IEC 61000-4-4, IEC 61000-4-5, Level 4 specifications.
- Immunity to Voltage Dips, Short Power Supply Interruptions and Voltage Variations meets and exceeds IEC 61000-4-11, Level 1 specifications.

**Physical and MTBF:**

- 1U, 19-Inch Industrial (IP50) Chassis.
- Optional, 1U, Ruggedized Industrial (IP61) Chassis.
- Height x Depth x Width: 44 mm x 250 mm x 482 mm
- Weight: 3 Kgs
- MTBF: ≥ 280,000 hours with dual redundant power supplies

**Ordering Information**

Product	Enigmättron-C-RFW
Part No.	VCL-2142RFW-yy
Description	Router, Data Encryption and Firewall Equipment
Power	yy: AC or DC

Technical specifications are subject to changes without notice.

All brand name and trademarks are the property of their respective owners.

Revision 2.4 - September 17, 2018

U.K.

Valiant Communications (UK) Ltd  
Central House Rear Office  
124 High Street, Hampton Hill  
Middlesex, TW12 1NS, U.K.

E-mail: gb@valiantcom.com

U.S.A.

Valcomm Technologies Inc.  
4000 Ponce de Leon, Suite 470  
Coral Gables, FL 33146  
U.S.A.

E-mail: us@valiantcom.com

INDIA

Valiant Communications Limited  
71/1, Shivaji Marg,  
New Delhi - 110015,  
India

E-mail: mail@valiantcom.com